



**A residue free, high dielectric strength (50,000V), fast drying solvent degreaser.**

### KEY PROPERTIES

- Dries quickly and residue free
- Effective in cleaning a wide range of oils, greases and fluxes.
- Safe for use on electric motors, windings, circuit boards and precision engineering components.
- High dielectric strength – 50,000V
- Harmless on plastics, rubbers, elastomers and painted surfaces (may swell some soft seals)

### APPLICATION

- Excellent for cleaning precision metal or plastic components and electrical components.
- Can be used as supplied in dip tanks, spray machines and ultrasonic baths.
- Available in trigger spray for bench top use.
- Not recommended for use on live equipment.
- For advice on application, please call +44 (0) 1561 361515.

### TECHNICAL DATA

Appearance	Clear colourless liquid	SG	Approx. 0.76
Flash Point	> 62°C (closed cup)	VOC Content	100%

### PACKAGING

12 x 0.5L trigger sprays, 4 x 5L, 25L, 200L, 1000L containers.

### SAFE HANDLING AND STORAGE

Store in original containers and avoid extremes of temperature.  
For guidance on handling and disposal, see Safety Data Sheet.

Manufactured and supplied by  
**Oil Technics Ltd.**  
Linton Business Park, Gourdon,  
Aberdeenshire, Scotland UK DD10 0NH  
**Tel:** +44 (0) 1561 361515  
**Fax:** +44 (0) 1561 361001  
**Email:** info@oiltechnics.com  
**Web:** www.oiltechnics.com



FM 696382 EMS 696323

