

Rust Stain Remover



RSR is designed for the removal of fresh rust and rust stains from ferrous material, prior to coating.

RSR's effective blend of inorganic acids quickly removes rust to leave a semi-passivated surface. Also suitable for use in removing carbonate scale.

- Non-fuming
- Short term corrosion protection
- Water rinsable

HOW TO USE

- For use on ferrous material and alloys.
- Apply neat by brush or via immersion soak tanks.
- Can be diluted in water up to 10% dilution (1 part RSR to 9 parts water).
- Rinse clean with water after application and before subsequent treatment of cleaned surfaces.

PHYSICAL PROPERTIES

Appearance	Pale yellow liquid
Specific gravity	1.16
pH	~2.0
Flash point (°C)	>93
VOC content	Negligible

TRANSPORT INFORMATION

UN Number: 3264
 Proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.
 Hazard Class: 8 Packing group: III

DISPOSAL

Dispose of excess product according to your local regulations. Containers should be rinsed before recycling.

ENVIRONMENTAL IMPACT

- Biodegradable
- Negligible VOC content
- No bioaccumulation potential

STORAGE AND SHELF LIFE

Best stored as supplied in original, unopened containers, off the ground and out of direct sunlight.

Do not expose to temperature extremes and prevent contamination from foreign materials. Shelf life: 4 years from Date of Manufacture. For further guidance on handling and storage, see Safety Data Sheet.

TECHNICAL SERVICES & SALES SUPPORT

For our UK customers, our products are available 24/7 via our 24 hour emergency call out service: +44 (0) 1561 361515.

Oil Technics Ltd manufacture in Scotland under ISO 9001:2015 and ISO 14001: 2015 accredited management systems.

PACK SIZES

- 4 x 5 Litre containers
- 20 litre containers
- 200 litre drums
- 1000 litre IBCs



Oil Technics Ltd

Linton Business Park, Gourdon, Aberdeenshire, Scotland UK DD10 0NH | +44 (0) 1561 361515 | info@oiltechnics.com | oiltechnics.com



Part of the OTL Group of Companies

